



# Clinical Research Chart Cell Installation Guide (Linux)

**Release 1.4**

*Document Version:* 1.6  
*i2b2 Software Version:* 1.4

# Table of Contents

<i>About this Guide</i>	<i>iii</i>
<i>Document Version History</i>	<i>iii</i>
<i>Prerequisites</i>	<i>1</i>
Required Software	1
<i>Install</i>	<i>4</i>
Installing the Clinical Research Chart Application	4
Changing Server log level	12
<i>Verify Installation</i>	<i>13</i>
CRC Cell Sanity Test via the i2b2Workbench	13
<i>License</i>	<i>17</i>

## About this Guide

Informatics for Integrating Biology and the Bedside (i2b2) is one of the sponsored initiatives of the NIH Roadmap National Centers for Biomedical Computing (<http://www.bisti.nih.gov/ncbc/>). One of the goals of i2b2 is to provide clinical investigators broadly with the software tools necessary to collect and manage project-related clinical research data in the genomics age as a cohesive entity—a software suite to construct and manage the modern clinical research chart. This guide with the provided source code will help you deploy an i2b2 cell.

## Document Version History

Date	Revision	Description	Author(s)
10/26/2007	1.0	Version 1.0	Rajesh Kuttan, Lori Phillips
06/30/2008	1.1	Added multiple data source lookup configuration based on domain, project and user.  JBoss data source configuration change.(XA to Local transaction).  CRCApplicationContext.xml property change.	Rajesh Kuttan
8/20/2008	1.2	Uploader service install added	Rajesh Kuttan
8/27/2008	1.3	Updated JBOSS version	Lori Phillips
9/24/2008	1.4	FileRepository integration with CRC Uploader added.	Rajesh Kuttan
10/20/2008	1.5	Added info for two projects	Lori Phillips
10/30/2009	1.6	Added CRC service account Added analysis plug-in setup 1.4 Release	Rajesh Kuttan

# 1

## Prerequisites

### ***Required Software***

If you installed the prerequisite software from the Hive Installation Guide you may skip this section.

#### **a. Java JDK**

##### **JDK 6.0 (recommended)**

Download JDK 6.0 Update 16 (jdk-6u-16-linux-i586.bin) from <http://java.sun.com/products/>

a) Install the SDK into a directory of your choice (/opt/java/jdk1.6.0\_16, YOUR\_JAVA\_HOME\_DIR)

#### **b. JBoss 4.2.2GA**

Download 'jboss-4.2.2.GA.zip', from <http://labs.jboss.com/jbossas/downloads>.

a) Unzip jboss-4.2.2.GA.zip into a directory of your choice (/opt/jboss-4.2.2.GA or YOUR\_JBOSS\_HOME\_DIR)

b) Set JBoss JVM to run with 1GB extended memory.

Edit 'YOUR\_JBOSS\_HOME\_DIR/bin/run.conf' and change the JAVA\_OPTS memory settings to that shown below. (-Xms512m, -Xmx1024m)

```
#
# Specify options to pass to the Java VM.
#
if [ "x$JAVA_OPTS" = "x" ]; then
    JAVA_OPTS="-Xms512m -Xmx1024m
-Dsun.rmi.dgc.client.gcInterval=3600000
-Dsun.rmi.dgc.server.gcInterval=3600000"
fi
```

c) If default port 8080 is unavailable (another application is using this port), edit 'YOUR\_JBOSS\_HOME\_DIR/server/default/deploy/jboss-web.deployer/server.xml' file to reconfigure the non-SSL HTTP/1.1 Connector to another port such as 9090

```
<!--Define a non-SSL HTTP/1.1 Connector on port 9090 →  
<Connector port="9090" address="${jboss.bind.address}"  
    maxThreads="250" maxHttpHeaderSize="8192"  
    emptySessionPath="true" protocol="HTTP/1.1"  
    enableLookups="false" redirectPort="8443"  
    acceptCount="100" connectionTimeout="20000"  
    disableUploadTimeout="true" />
```

```
<!--Define an AJP 1.3 Connector on port 9009 →  
<Connector port="9009" address="${jboss.bind.address}"  
    maxThreads="250" maxHttpHeaderSize="8192"  
    protocol="AJP/1.3" emptySessionPath="true"  
    enableLookups="false" redirectPort="8443"/>
```

### c. Apache Ant 1.6.5

Download 'Apache Ant version 1.6.5' (apache-ant-1.6.5-bin.zip) from <http://archive.apache.org/dist/ant/binaries/>

a)Unzip into a directory of your choice (/opt/apache-ant-1.6.5 or YOUR\_ANT\_HOME\_DIR)

### d. Apache Axis2 1.1

Download 'Apache Axis2 version 1.1', from [http://ws.apache.org/axis2/download/1\\_1/download.cgi](http://ws.apache.org/axis2/download/1_1/download.cgi) and select the download type WAR (Web Archive) Distribution.(axis2.war)

a)Create folder i2b2.war inside  
'YOUR\_JBOSS\_HOME\_DIR/server/default/deploy'

b)Unzip axis2.war inside  
'YOUR\_JBOSS\_HOME\_DIR/server/default/deploy/i2b2.war' folder.

### **e. Oracle Express Edition**

a) Download Oracle Database 10gExpress Edition (Universal) 'oracle 10g EE' 'oracle-xe-univ-10.2.0.1-1.0.i386.rpm' from <http://www.oracle.com/technology/software/products/database/xe/htdocs/102xeinsoft.html>

b) Run 'rpm -i oracle-xe-univ-10.2.0.1-1.0.i386.rpm' as root

Run '/etc/init.d/oracle-xe configure' as root to configure the database

Select HTTP and listener ports (use defaults 8080/1521 if they are available)

Select 'Y'es to start on boot when asked

c) To verify that Oracle was properly installed, open a browser and enter <http://yourHost:yourPort/apex>. You should see an Oracle Database Express Edition login screen.

### **f. CVS client**

If installing application source code from CVS, make sure \$CVSROOT variable is pointed to phsi2b2appdev's /cvs/repository  
(ext:tomcat@phsi2b2appdev.mgh.harvard.edu:/cvs/repository)

### **g. Update your environment variables**

Be sure to set the JAVA\_HOME, ANT\_HOME and JBOSS\_HOME variables to the JAVA, ANT and JBOSS home directories you set up in steps a-c respectively. Examples are shown below.

```
# Sample environment variables
JAVA_HOME=/opt/java/jdk1.6.0_16
ANT_HOME=/opt/apache-ant-1.6.5
JBOSS_HOME=/opt/jboss-4.2.2.GA
PATH=$PATH:$ANT_HOME/bin:$JAVA_HOME/bin
export JBOSS_HOME
export ANT_HOME
export JAVA_HOME
```

### **h. Data installation or upgrade has already been performed.**

# 2

## Install

### ***Installing the Clinical Research Chart Application***

#### **1. Download and extract the core server source code to a target area.**

If this has been downloaded in a previous installation (e.g. PM or ONT), there is no need to repeat this step.

- a) Set up a target source\_directory.
- b) Extract core server source code to the target source\_directory.

#### **2. Ensure that JBOSS is not running**

- a) `./$JBOSS_HOME/bin/shutdown.sh -S`

#### **3. Deploy edu.harvard.i2b2.common**

If this has been deployed in a previous installation (eg. ONT), there is no need to repeat this step.

- a) `'cd source_directory/edu.harvard.i2b2.common'`
- b) Edit the build.properties file and set jboss.home and axis2.war.name properties

```
jboss.home=YOUR_JBOSS_HOME_DIR  
axis2.war.name=i2b2.war
```

- c) `'ant clean dist deploy jboss_pre_deployment_setup'`

## 4. Deploy edu.harvard.i2b2.crc and edu.harvard.i2b2.crc.loader

### 4.1. Build edu.harvard.i2b2.crc.loader

The Uploader service is added to the CRC as part of the Release 1.3. The source for the Uploader resides in edu.harvard.i2b2.crc.loader project and it uses the CRC's datasource setup.

a) 'cd source\_directory/edu.harvard.i2b2.crc.loader'

b) Edit the build.properties file and set jboss.home and axis2.war.name properties

```
jboss.home=YOUR_JBOSS_HOME_DIR
axis2.war.name=i2b2.war
```

c) Edit the etc/spring/crc\_loader\_application\_directory.properties file and specify a location for the application properties directory. This location can be anything you desire but must be a directory path that your linux user has access permission for.

```
edu.harvard.i2b2.crc.applicationdir= YOUR_JBOSS_HOME_DIR
/server/default/conf/crcloaderapp
```

d) Edit the etc/spring/edu.harvard.i2b2.crc.loader.properties file and set project management properties

Set Project Management property settings:

Note the new location of the PM URL.

```
edu.harvard.i2b2.crc.loader.ws.pm.url=http://localhost:9090
/i2b2/rest/PMService/getServices
# Flag to bypass project management cell
edu.harvard.i2b2.crc.loader.ws.pm.bypass=false
edu.harvard.i2b2.crc.loader.ws.pm.bypass.role=ADMIN
edu.harvard.i2b2.crc.loader.ws.pm.bypass.project=Demo
```

If you are using file repository cell and want to connect the CRC loader to it, then set the FileRepository cell property setting

```
#####
# File Management Cell
#####
edu.harvard.i2b2.crc.loader.ws.fr.url=http://localhost:9090/
i2b2/services/FRService/
```

e) Edit the etc/spring/CRCLoaderApplicationContext.xml

Specify the jdbc properties to locate the 'CRC\_DB\_LOOKUP' table.

```
<bean id="LoaderLookupDS" class="org.apache.commons.dbcp.BasicDataSource" destroy-
method="close">
    <property name="driverClassName" value=" oracle.jdbc.driver.OracleDriver"/>
    <property name="url" value="jdbc:oracle:thin:@localhost:1521:xe"/>
    <property name="username" value="i2b2hive"/>
    <property name="password" value="i2b2hive_pswd"/>
</bean>
```

Update entry in edu.harvard.i2b2.crc.loader.properties to reflect the above change.

```
#####
# Datasource Lookup properties
#####
edu.harvard.i2b2.crc.loader.ds.lookup.datasource=LoaderLookupD
```

S

```
edu.harvard.i2b2.crc.loader.ds.lookup.srvtype=ORACLE
edu.harvard.i2b2.crc.loader.ds.lookup.schemaname=i2b2hive
```

f) 'ant -f build.xml clean dist'

Note : No 'deploy' target is used. The loader will be deployed as part of edu.harvard.i2b2.crc project.

## 4.2 Setup edu.harvard.i2b2.crc

a) 'cd source\_directory/edu.harvard.i2b2.crc'

b) Edit the build.properties file and set jboss.home and axis2.war.name properties

```
jboss.home=YOUR_JBOSS_HOME_DIR
axis2.war.name=i2b2.war
#jms persistence could be either oracle or mssql
jboss.jms.persistence=oracle
```

c) Edit the etc/spring/crc\_application\_directory.properties file and specify a location for the application properties directory. This location can be anything you desire but must be a directory path that your linux user has access permission for.

```
edu.harvard.i2b2.crc.applicationindir= YOUR_JBOSS_HOME_DIR
/server/default/conf/crcapp
```

d) Edit the etc/spring/crc.properties file and set project management properties

Set Project Management property settings

Note the new location of the PM Service.

```
#####
# Project Management Cell
#####
queryprocessor.ws.pm.url=http://localhost:9090/i2b2/rest/PMService/getServices
# Flag to bypass project management cell
queryprocessor.ws.pm.bypass=false
queryprocessor.ws.pm.bypass.role=ADMIN
queryprocessor.ws.pm.bypass.project=Demo
```

e)Set Ontology property settings, change the hostname and port

```
#####
# Ontology Cell
#####
queryprocessor.ws.ontology.url=http://localhost:9090/i2b2/rest/OntologyService/getTermInfo
```

f)Create the CRC service user account in the Project Management cell and assign the 'User' and 'Data\_Obfsc' role to the user. CRC uses this PM user in the Ontology and PM cell calls.

```
#####
# CRC service account properties
#####
edu.harvard.i2b2.crc.pm.serviceaccount.user=
OBFSC_SERVICE_ACCOUNT
edu.harvard.i2b2.crc.pm.serviceaccount.password=
demouser
```

g) Update QT\_BREAKDOWN\_PATH table: Based on your Ontology mapping, update the parent item key values used in the analysis break down calculation.

Name	Value
PATIENT_GENDER_COUNT_XML	\\i2b2\i2b2\Demographics\Gender\
PATIENT_RACE_COUNT_XML	\\i2b2\i2b2\Demographics\Race\
PATIENT_VITALSTATUS_COUNT_XML	\\i2b2\i2b2\Demographics\Vital Status\
PATIENT_AGE_COUNT_XML	\\i2b2\i2b2\Demographics\Age\

h) The following steps tells CRC, where the "CRC\_DB\_LOOKUP" table is located.

code_lookup		
PK	<u>c_domain_id</u>	varchar(255)
PK	<u>c_project_path</u>	varchar(255)

code_lookup		
PK	<u>c_owner_id</u>	varchar(255)
	<b>c_db_fullschema</b>	<b>varchar(255)</b>
	<b>c_db_datasource</b>	<b>varchar(255)</b>
	<b>c_db_servertype</b>	<b>varchar(255)</b>
	<b>c_db_nicename</b>	<b>varchar(255)</b>
	c_db_tooltip	varchar(255)
	c_comment	text
	c_entry_date	datetime
	c_change_date	datetime
	c_status_cd	char(1)

Edit etc/spring/CRCApplicationContext.xml:

```
<bean id="CRCDataSourceLookup"
class="org.apache.commons.dbcp.BasicDataSource" destroy-
method="close">
  <property name="driverClassName" value="
    oracle.jdbc.driver.OracleDriver"/>
  <property name="url"
    value="jdbc:oracle:thin:@localhost:1521:xe"/>
  <property name="username" value="i2b2hive"/>
  <property name="password" value="i2b2hive_pswd"/>
</bean>
```

Update entry in etc/spring/crc.properties to reflect the above change.

```
#####
# Datasource Lookup properties
#####
queryprocessor.ds.lookup.datasource=CRCDataSourceLookup
queryprocessor.ds.lookup.servertype=ORACLE
queryprocessor.ds.lookup.schemaname=i2b2hive
```

Continuing in file etc/spring/crc.properties:

i)The PDO paging size can be adjusted based on the runtime jvm setting.

```
#####
# PDO Paging properties
#####
edu.harvard.i2b2.crc.pdo.paging.observation.size=75000
```

j)You can tune the default max job count for the Analysis job queue

```
#####
# Analysis Queue properties
#####
edu.harvard.i2b2.crc.analysis.queue.medium.timeoutmills=1800000
edu.harvard.i2b2.crc.analysis.queue.medium.maxjobcount=4
edu.harvard.i2b2.crc.analysis.queue.large.timeoutmills=3600000
```

```
edu.harvard.i2b2.crc.analysis.queue.large.maxjobcount=4
edu.harvard.i2b2.crc.analysis.queue.medium.jobcheck.timemills=120000
edu.harvard.i2b2.crc.analysis.queue.large.jobcheck.timemills=120000
```

k)If required adjust the default query queues timeout in second.

```
#####
# Setfinder JMS Queue transaction timeout properties
#####
edu.harvard.i2b2.crc.jms.small.timeoutsec=180
edu.harvard.i2b2.crc.jms.medium.timeoutsec=14400
edu.harvard.i2b2.crc.jms.large.timeoutsec=43200
```

l)If required change the default user's setfinder lockout parameter

```
#####
# CRC setfinder query lockout parameter
#####
edu.harvard.i2b2.crc.lockout.setfinderquery.count=7
edu.harvard.i2b2.crc.lockout.setfinderquery.day=30
```

m)Configure JBoss Datasource:

CRC supports both Oracle and SqlServer. Edit etc/jboss/crc-ds.xml and set the database connection properties. For SqlServer data source, please use the sample provided in the crc-ds.xml.

The following steps show the configuring Oracle data source for two projects. If your setup has multiple projects pointing to different data sources, then copy <local-tx-datasource> in ds-xml for each project data source.

```
<jndi-name>QueryToolDemoDS</jndi-name>
<connection-
url>jdbc:oracle:thin:@localhost:1521:xe</connection-url>
<driver-class>oracle.jdbc.driver.OracleDriver</driver-class>
<user-name>i2b2demodata</user-name>
<password>i2b2demodata_password</password>
```

For example, project Demo2 would have this entry:

```
<jndi-name>QueryToolDemo2DS</jndi-name> with connection-url:

<connection-
url>jdbc:oracle:thin:@localhost:1521:xe</connection-url>
<driver-class>oracle.jdbc.driver.OracleDriver</driver-class>
<user-name>i2b2demodata2</user-name>
<password>i2b2demodata2_password</password>
```

n)Edit etc/jboss/crc-jms-ds.xml and set 'DefaultDS' JMS database connection properties. If the data source is Sqlserver, then comment the oracle section and uncomment sqlserver datasource section.

```

<local-tx-datasource>
  <jndi-name>DefaultDS</jndi-name>
  <connection-
url>jdbc:oracle:thin:@localhost:1521:xe</connection-url>
  <driver-class>oracle.jdbc.driver.OracleDriver</driver-
class>
  <user-name>i2b2hive_uname</user-name>
  <password>i2b2hive_password</password>
  ...
</local-tx-datasource>

```

### 4.3 Build and deploy edu.harvard.i2b2.crc and edu.harvard.i2b2.crc.loader

‘ant -f master\_build.xml clean build-all deploy’

**Note: If you are deploying on an existing JBoss instance with CRC 1.3, then please remove the QueryProcessor-EJB.jar from the \$JBOSS\_HOME/server/default/deploy directory.**


### 5. Start JBOSS

a) Run ‘\$JBOSS\_HOME/bin/run.sh -b 0.0.0.0’

### 6. Verify webservice is running

a) Check url ‘http://yourHost:9090/i2b2/services/listServices’ in a browser.

Verify that QueryToolService is listed as active.



## Changing Server log level

By default JBOSS log will be in DEBUG mode, changing it to INFO mode will increase server performance.

- a) Edit \$JBOSS\_HOME/server/default/conf/jboss-log4j.xml file and add the 'Threshold' <param>.

```
<appender name="FILE"
class="org.jboss.logging.appender.DailyRollingFileAppender">
  <errorHandler
class="org.jboss.logging.util.OnlyOnceErrorHandler"/>
  <param name="File"
value="${jboss.server.home.dir}/log/server.log"/>
  <param name="Append" value="false"/>
  <param name="Threshold" value="INFO"/>
  <!-- Rollover at midnight each day -->
  <param name="DatePattern" value="'.'yyyy-MM-dd"/>

  <layout class="org.apache.log4j.PatternLayout">
    <!-- The default pattern: Date Priority [Category] Message\n -
->
    <param name="ConversionPattern" value="%d %-5p [%c] %m%n"/>

    . . . . .
  </layout>
</appender>
```

To switch back to DEBUG mode, comment out the 'Threshold' <param> and wait a minute. THERE IS NO NEED TO RESTART JBOSS.

# 3

## Verify Installation

### ***CRC Cell Sanity Test via the i2b2Workbench***


#### **1. Configure the i2b2Workbench to communicate with your CRC cell.**

Cell configuration is addressed in the Project Management (PM) Cell installation and set up. Please refer to this document if the CRC Cell has not yet been configured.

To verify this data, go to the web client site <http://host/webclient>.

Once logged on, select 'Cells' under the 'Hive primary navigation tab. If the CRC Cell has been configured it will be listed as an existing, registered cell:

To verify cell data, select cell name(CRC) and click on Edit Cell Info.




#### **2. Launch the i2b2Workbench (double-click on i2b2Workbench.exe)**

Login to i2b2:

- a. Select your target location (YourSite)
  - b. Enter a valid username and password (demo/demouser)
  - c. The URL at the bottom of the login screen should be the address of your PM cell.
- If not, edit the i2b2workbench.properties file to point to the location of your PM cell.


I2b2.1=YourSite,REST,http://jbossHost:port/i2b2/rest/PMService/



The image shows a Java-style dialog box titled "Login to i2b2". Inside the dialog, the text "Enter User ID and Password" is centered. Below this, there are three input fields: "Target location:" with a dropdown menu showing "YourSite", "User name:" with a text box containing "demo", and "Password:" with an empty text box. Below the password field is a checkbox labeled "Start as demonstration only" which is unchecked, and a small button with a question mark "?". At the bottom of the input section are two buttons: "Login" and "Cancel". At the very bottom of the dialog, there is a text box containing the URL "http://jbossHost:port/i2b2/rest/PMService/".

### 3. Open the Query Tool, Previous Queries and Timeline views in the workbench

If all is configured properly, you will be greeted with the following



#### 4. Possible problems

a. Error message appears in view window.

- ‘CRC cell is unavailable’:

CRC cell address in the PM webclient is incorrect (see step 1 of this section) or  
CRC Cell may be down:  
Check url ‘http://yourHost:9090/i2b2/services/listServices’ in a browser.  
Verify that QueryToolService is listed as active.

- ‘Remote server is unavailable’:

Server may be down.  
Check url ‘http://yourHost:9090/i2b2/services/listServices’ in a browser.  
Verify that QueryToolService is listed as active.

- ‘PM service is not responding’:

Project Management Cell is down or its address was not configured properly in  
section 2 step 4.1.d or step 4.2.d.

- ‘Database error’:

There are problems connecting to the database.  
Verify database configuration parameters in section 2 steps 4.1 and 4.2.

# 4

## License

The i2b2 source code is licensed under the i2b2 Software License Software. This includes but not limited to all code in the `edu.harvard.mgh.i2b2.*` package namespace.