

## ,webclient-cas.PATCH

```
diff -r c3ba49d2a1b2 -r 61c9bad49479 webclient/default.htm
--- a/webclient/default.htm    Mon Apr 19 00:00:00 2010 -0500
+++ b/webclient/default.htm    Fri Aug 27 09:04:50 2010 -0500
@@@ -102,7 +102,8 @@
                                         // by editing the CSS file. You can remark out the lines
below with no ill effect. Use the following
                                         // javascript function to display the modal login form:
i2b2.hive.PM.doLoginDialog();

//cellObj.doConnectForm($('loginusr'),$('loginpass'),$('logindomain'), $('loginsubmit'));
-
-                         i2b2.PM.doLoginDialog();
+
+                         var domain = 'localhost'; //@@@HARDCODED
+
+                         i2b2.PM.doCASLogin(domain);
+
+                         break;
}
})
diff -r c3ba49d2a1b2 -r 61c9bad49479 webclient/js-i2b2/cells/PM/PM_ctrlr.js
--- a/webclient/js-i2b2/cells/PM/PM_ctrlr.js    Mon Apr 19 00:00:00 2010 -0500
+++ b/webclient/js-i2b2/cells/PM/PM_ctrlr.js Fri Aug 27 09:04:50 2010 -0500
@@@ -87,6 +87,8 @@
try {
    var t = i2b2.h.XPath(data.refXML, '//user/password')[0];
    i2b2.PM.model.login_password = i2b2.h.Xml2String(t);
+
    t = i2b2.h.XPath(data.refXML, '//user/user_name/text()')[0];
+
    i2b2.PM.model.login_username = i2b2.h.Xml2String(t);
} catch (e) {
    console.error("Could not find returned password node in login XML");
    i2b2.PM.model.login_password =
"<password>" + data.msgParams.sec_pass + "</password>\n";
@@@ -495,4 +497,4 @@

console.timeEnd('execute time');
-
-console.groupEnd();
\ No newline at end of file
+console.groupEnd();
diff -r c3ba49d2a1b2 -r 61c9bad49479 webclient/js-i2b2/cells/PM/cas_login.js
--- /dev/null    Thu Jan 01 00:00:00 1970 +0000
+++ b/webclient/js-i2b2/cells/PM/cas_login.js      Fri Aug 27 09:04:50 2010 -0500
@@@ -0,0 +1,109 @@
+/*
+ * i2b2 login using a CAS ticket as the credential in place of a password.
+ *
+ * @author: Dan Connolly <dconnolly@kumc.edu>
+ *
+ * umm... not sure what these mean...
+ * @inherits i2b2
+ * @namespace      i2b2
```

```

+ *
+ * @todo: figure out what to do if PM:Login fails; maybe include a link
+ *      back to the portal or something?
+ */
+
+/* see JSLint, The JavaScript Code Quality Tool http://www.jslint.com/ */
+/*jslint browser: true, undef: true, strict: true */
+/*global alert */
+/*global i2b2, i2b2_scopedCallback */
+"use strict";
+
+/**
+ * doCASLogin gets username, ticket, and domain from URL and calls PM:Login
+ */
+i2b2.PM.doCASLogin = function(domainname) {
+  var match, i;
+  var adr = location.href;
+
+  var service = adr.split("?")[0];
+
+  match = /ticket=([^&#]*).exec(adr);
+  var ticket = match ? match[1] : null;
+  if (!ticket) {
+    // alert()? that's how we're doing error handling? hmm.
+    alert("login failed: no CAS ticket URL parameter");
+    return;
+  }
+
+  var domain, domains = i2b2.PM.model.Domains;
+  for (i = 0; i < domains.length; i++) {
+    if (domains[i].name == domainname) {
+      domain = domains[i];
+      break;
+    }
+  }
+  if (!domain) {
+    alert('login failed: no such domain in i2b2 config: ' + domainname);
+    return;
+  }
+
+  i2b2.PM.model.url = domain.urlCellPM;
+  i2b2.PM.model.allow_analysis = _flag(domain.allowAnalysis, true);
+  i2b2.PM.model.login_debugging = _flag(domain.debug, true);
+
+  i2b2.h.LoadingMask.show() // GUI goes busy
+
+  var callback = new i2b2_scopedCallback(i2b2.PM._processUserConfig, i2b2.PM);
+  var parameters = {
+    domain: domain.domain,
+    is_shrine: Boolean.parseTo(domain.isSHRINE),
+    project: domain.project,

```

```

+
+     username: service,
+     password_text: ticket
+   };
+   var transportopts = {
+     url: domain.urlCellPM,
+     user: service,
+     password: ticket,
+     domain: domain.domain,
+     project: domain.project
+   };
+
+   _make_dialog();
+   i2b2.PM.ajax.getUserAuth("PM:Login", parameters, callback, transportopts);
+};
+
+
+function _flag(expr, fallback){
+  if (expr != undefined) {
+    return Boolean.parseTo(expr);
+  } else {
+    return fallback;
+  }
+}
+
+
+/*
+ * i2b2.PM._processUserConfig assumes the dialog exists, so...
+ */
+function _make_dialog() {
+  if (!$("i2b2_login_modal_dialog")) {
+    var htmlFrag = i2b2.PM.model.html.loginDialog;
+    Element.insert(document.body,htmlFrag);
+
+    if (!i2b2.PM.view.modal.login) {
+      i2b2.PM.view.modal.login = new YAHOO.widget.Panel("i2b2_login_modal_dialog", {
+        zindex: 700,
+        width: "501px",
+        fixedcenter: true,
+        constraintviewport: true,
+        close: false,
+        draggable: true
+      });
+      // connect the form to the PM controller
+      i2b2.PM.udlogin = {};
+      i2b2.PM.udlogin.inputUser = $('#loginusr');
+      i2b2.PM.udlogin.inputPass = $('#loginpass');
+      i2b2.PM.udlogin.inputDomain = $('#logindomain');
+    }
+  }
+}
+
diff -r c3ba49d2a1b2 -r 61c9bad49479 webclient/js-i2b2/cells/PM/cell_config_data.js

```

```
--- a/webclient/js-i2b2/cells/PM/cell_config_data.js Mon Apr 19 00:00:00 2010 -0500
+++ b/webclient/js-i2b2/cells/PM/cell_config_data.js Fri Aug 27 09:04:50 2010 -0500
@@@ -7,7 +7,8 @@
    "PM_ctrlr.js",
    "PM_admin_ctrlr.js",
    "PM_admin_view.js",
-
    "i2b2_msgs.js"
+
    "i2b2_msgs.js",
+
    "cas_login.js"
],
css: ["modProjects.css"], // ONLY USE 1 STYLE SHEET:
http://support.microsoft.com/kb/262161
config: {
```